**Product Overview** 

You are currently viewing:




**Heavy Duty Modular** Conveyors



Parallel Shaft/ Flange Drives ...... IN-PAR



**RNG Easy Access** Dial Indexers ..... IN-RNG





Servo Positioner Rotary Table ......IN-GTB



Rite-Link Conveyors ...... IN-RLC



RDM Dial Indexers ...... IN-RDM



Table-Top Modular Conveyors ...... IN-TTC



RA Right Angle Drives ...... IN-RA



LPP Linear Part Handles ...... IN-LPP



RD HD Dial Indexers ..... IN-RD



RPP Rotating Part Handlers .. IN-RPP



E-Series HD Drives ...... IN-EHD



Overload Clutches ...... IN-CLU



MDE/HDE Indexers ...... IN-MDE



Custom Cams ...... IN-CAM



RSD Flexible Servo Drives .. IN-RSD



RGS/RGD Shaft/Flange Drives ...... IN-RGS

Features | Table of Contents



#### **Features:**

CAMCO Heavy Duty Precision Link Conveyors combine excellent accuracy with high load capacity to provide the versatility needed to meet virtually any automated assembly or manufacturing challenge.

Standard link lengths of 6.0", 9.0" and 12"

Over/Under and Carousel configurations

Precision links with roller bearing cam followers for smooth transfer and long life

Provided with heavy-duty legs and a precision machined base designed to hold large loads and maintain system accuracy

Available with adjustable soft machine mounts to accommodate inconsistent on-site flooring

Customize length and height and add optional line shafts or tooling plates to fit your application

### **Table of Contents**

How to Order	3
Conveyor Options	4
6.0 Inch Heavy Duty	5
9.0 Inch Heavy Duty	7
12.0 Inch Heavy Duty	9

How To Order

### **Required Information**

- Link Size: 1.5, 2.0, 3.0, 4.5, 6.0, 9.0 or 12.0
- Type: Table Top or Heavy Duty
- Style: Over/Under or Carousel
- · Length: Standard per catalog or Custom, expressed as center distance, in inches
- Height: Standard per catalog or Custom, in inches

#### **Technical Assistance**

All Precision Link Conveyor applications are verified by a IMC sales agent using the IMC Sizing Program.


Your IMC agent is available to make all sizing calculations for you.

# TAKE-UP END Length LEFT SIDE (SIDE 2) RIGHT SIDE (SIDE 1) **DRIVE END**

**OVER/UNDER** 

### **Required Information when ordering Drive Package**


- Type: Standard, Alternate, Heavy-Duty or Special
- Drive Side: 1 or 2 (for Over/Under)
- Index Distance: In inches
- Indexer Model: Specific model number or special



**CAROUSEL** 

#### **Options**

CAMCO offers a wide variety of standard and custom options on all precision link conveyers. Tooling plates and conveyor mainframes can be ordered with custom hole configurations or burnouts. Other standard options include timing chains, timing belts and extended lineshafts. Standard drive package options include CAMCO indexers with AC motors and clutch-brakes, DC motors or servo motors. CAMCO's special Indexer output overload clutches are highly recommended to protect the indexer, link assembly and tooling.




#### **Using Cambot Parts Handlers with Precision Link Conveyors**

Cambot linear pick-and-place parts handlers have custom cam motions incorporated into each unit, providing complex synchronize timings for your application. They can be mounted onto the backbone tooling plages of the conveyor. Cambot linear pick-and-place parts handlers can be belt driven off a common line shaft for perfect synchronization. See the Rotary Parts Handler section (page 181) for other possible configurations, such as a rotary pick-and-place device loading parts from a continuous line conveyor to a CAMCO index drive conveyor.



## Heavy Duty Modular Conveyors | Dimension

Link



## Modular Conveyor (drive package)


### Standard Drive Package

- 1301RD Intermittor
- 73500C Reducer
- 5 hp AC Motor
- MDB-1125 Air Clutch-Brake
- Cycle Cam & Limit Switch


Index Distance [in.]	Indexer Stops
6.00	12
12.00	6
18.00	4
24.00	3

### Heavy Duty Modular Conveyors | Configurations

#### Carousel




### Over/Under



Heavy Duty Modular Conveyors | Dimensions

Link



## Modular Conveyor (drive package)

### Standard Drive Package


- 1301RD Intermittor
- 73500C Reducer
- 5 hp AC Motor
- MDB-1125 Air Clutch-Brake
- Cycle Cam & Limit Switch

Index Distance [in.]	Indexer Stops
9.00	12
18.00	6
27.00	4
36.00	3




### Heavy Duty Modular Conveyors | Configurations

#### Carousel




<sup>\*</sup>Conveyor lengths can be customized for your application. Please consult factory.



#### CONVEYOR SHOWN WITH 10-TOOTH SPROCKET

### Over/Under




CONVEYOR SHOWN WITH 10-TOOTH SPROCKET



Heavy Duty Modular Conveyors | Dimensions

Link



### Modular Conveyor (drive package)

### Standard Drive Package


- 1301RD Intermittor
- 7500C Reducer
- 5 hp AC Motor
- MDB-1125 Air Clutch-Brake
- Cycle Cam & Limit Switch

Index Distance [in.]	Indexer Stops	Sprocket
12.00	8, 10, 12	8T, 10T, 12T
24.00	4, 5, 6	8T, 10T, 12T
36.00	4	12T
48.00	2, 3	8T, 12T




### Heavy Duty Modular Conveyors | Configurations

#### Carousel



<sup>\*</sup>Conveyor lengths can be customized for your application. Please consult factory.



#### Over/Under

